

# DUOLINE FELT

AMAZON

## DISPOSABLE NEEDLEFELT FILTER BAGS

**DuoLINE** filter bags have been designed to provide effective filtration for a wide range of applications using a variety of filter media. Manufactured with welded seams, to provide greater security over the more common stitched alternatives

**DuoLINE PP, PE, NY** and **NX** range filter bags adopt the use of needlefelt type media which provides both surface and depth filtration for maximum dirt capacity.

### Product Features

- Polypropylene, Polyester, Nylon and Nomex needlefelt media, rated between 1 - 200µm
- Wide chemical compatibility
- Double integral handles on all models
- FDA compliant material (PP Only)

**DuoLINE XP** filter bags are designed to give longer service life, therefore reducing operating costs and process downtime. The **XP** bags greater depth provides additional void volume resulting in a greater dirt holding capacity resulting in a longer life over standard needlefelt materials of up to 2-5 times.

### Product Features

- Polypropylene needlefelt media, rated 1 - 100µm
- Double integral handles on all models
- Extended life
- FDA compliant material

Three bag diameters are available in the **DuoLINE** range, 4¼, 5½ and 7" all fitted as standard with a top ring locator in various materials and styles.

All **DuoLINE** bags are designed to filter from the inside to out leaving the contamination inside the bag for simple disposal. These needlefelt bags can be used for both pre and final filtration duties.

Amazon Filters manufacture a comprehensive range of filter housings for the **DuoLINE** bags. Available in many materials and sizes to suit all flow rates, please consult our sales office for further details of the full range.



## DUOLINE FEATURES AND BENEFITS

- Micron ratings available from 1 to 200µm for wide ranging filtration needs
- Optional moulded polypropylene flange with handles for superior sealing and ease of handling
- Welded Needlefelt as standard for 4¼ and 7" ring sizes
- Wide selection of filter media and support ring materials
- Identification supplied with every bag
- Silicone free for use in automotive paint applications

DUOLINE FELT

## TECHNICAL DATA

### Maximum Operating Conditions

|             |       |         |
|-------------|-------|---------|
| Temperature | 19PP: | 95°C    |
|             | 19PE: | 135°C*1 |
|             | 19NY: | 135°C*1 |
|             | 19NX: | 190°C*1 |

Recommended Maximum Differential Pressure: 4 Bar

\*1 Bags adopting the use of a polypropylene sealing flange have a maximum operating temperature of 95°C.

### Dimensional Data

| Bag Size | Length (mm) | Ring Diameter (mm) | Capacity (Litres) | Surface Area (m <sup>2</sup> ) | Flow Rate (m <sup>3</sup> /hr)*2 |
|----------|-------------|--------------------|-------------------|--------------------------------|----------------------------------|
| 1M (P3)  | 200         | 108                | 1.8               | 0.068                          | 3                                |
| 2M (P4)  | 355         | 108                | 3.2               | 0.120                          | 6                                |
| 1A       | 420         | 140                | 6.4               | 0.185                          | 9                                |
| 2A       | 810         | 140                | 12.5              | 0.356                          | 18                               |
| 3A       | 1220        | 140                | 19.0              | 0.536                          | 28                               |
| 1G (P1)  | 420         | 178                | 10.0              | 0.235                          | 12                               |
| 2G (P2)  | 810         | 178                | 20.0              | 0.453                          | 25                               |
| 3G       | 1220        | 178                | 30.0              | 0.682                          | 40                               |

\*2 The flow rates quoted are our maximum recommended values for each bag type based on water, or liquid of a similar viscosity at ambient temperature. For advice on the filtration of liquids with greater viscosities please contact our sales office.

## INDUSTRIES AND APPLICATIONS

- |                 |   |
|-----------------|---|
| Pharmaceutical  | • Bulk transfer, Catalyst removal, Powder trap                                |
| Cosmetics       | • Creams, Lotions, Gels, Filling head trap filter                             |
| Metal Finishing | • Wash solutions, Paints, Resins, Varnishes                                   |
| Water Treatment | • Membrane protection (Reverse osmosis, nano), Resin trap, Potable water      |
| Automotive      | • Cooling fluid, Electrophoretic paints, Degreasing systems, Phosphate filter |
| Chemical        | • Bulk transfer lines, Tanker discharge and loading lines                     |
| Petrochemical   | • Amine and Glycol systems, Bulk kerosene processing, Solvent transfer lines  |

## AMAZON FILTERS LTD.

ALBANY PARK ESTATE, FRIMLEY ROAD,  
CAMBERLEY, SURREY, GU16 7PG  
ENGLAND

Tel: +44 (0) 1276 670 600

Fax: +44 (0) 1276 670 101

Email: [sales@amazonfilters.co.uk](mailto:sales@amazonfilters.co.uk)

Web: [www.amazonfilters.co.uk](http://www.amazonfilters.co.uk)



Certificate No. FM39584

Distributed by: